

---

**SAFETY DATA SHEET**

---

**Section 1: IDENTIFICATION**

**Product Name:** Reducer #1 - Thinner PL

**Product Code:** 110-001

**MSDS Date:** June 24, 2018

Manufactured for: Multi-Tech, Inc.  
5101 Penrose St.  
St. Louis, MO 63115

**General Information:** 314-382-9881

**CHEMTREC:** 800-424-9300

**Section 2: HAZARDS IDENTIFICATION****EMERGENCY OVERVIEW****GHS Classification:**

Flammable liquid, (Category 4)

Acute Toxicity - Inhalation (Category 4)

Skin irritation, (Category 2)

Eye irritation, (Category 2B)

Specific Target Organ Toxicity, Single Exposure (Category 3)

**GHS Labeling**

**Symbol:**

**Signal Word:** Warning

**Hazard Statements:**

Combustible liquid

Harmful if inhaled

Causes skin irritation.

Causes eye irritation

May cause drowsiness or dizziness

**Precautionary Statements:****Prevention:**

Avoid breathing mist/vapors/spray.

Keep away from flames and hot surfaces-no smoking.

Use only outdoors or in a well-ventilated area.

Wash thoroughly after handling.

Wear protective gloves/eye protection/face protection

**Response:**

Call a poison center/doctor if you feel unwell.

If eye irritation persists: Get medical advice/attention.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If inhaled: Remove person to fresh air and keep comfortable for breathing.

If on skin: Wash with plenty of water.

If skin irritation occurs: Get medical advice/attention.

In case of fire: Use water fog. Foam. Carbon dioxide (CO2). Alcohol resistant foam. Powder. Dry chemicals to extinguish.

Take off contaminated clothing and wash it before reuse.

**Storage:**

Store in a well-ventilated place. Keep cool. Keep container tightly closed.

Store locked up

**Disposal:**

Dispose of contents/container in accordance with local/regional/national/international regulations.

**Potential Health Effects:** See Section 11 for more information

This product does not contain carcinogens or potential carcinogens as listed by NTP or ACGIH.

This material contains components that are considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

**Potential Environmental Effects:** See Section 12 for more information.

### Section 3: COMPOSITION/INFORMATION ON INGREDIENTS

No.	Component CAS REG. NO.	Amount %	OSHA		ACGIH	
			TWA	STEL	TWA	STEL
1	Hydrotreated Light Distillates (petroleum) CAS # 64742-47-8	1-100	Not Avail	Not Avail	200 ppm	Not Avail

### Section 4: FIRST AID MEASURES

**Emergency first aid procedures by route of exposure:**

**Inhalation:** Move exposed person to fresh air. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. Loosen tight clothing such as a collar, tie, belt or waistband. Get medical attention immediately.

**Ingestion:** Wash out mouth with water. Do not induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get medical attention immediately.

**Skin:** In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash clothing before reuse. Clean shoes thoroughly before reuse. Get medical attention immediately.

**Eyes:** Check for and remove any contact lenses. Immediately flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Get medical attention immediately.

**Note to physician:** Symptoms may be delayed

### Section 5: FIRE FIGHTING MEASURES

**Flash Point (Hydrotreated Light Distillates):** >142°F (TCC) = 61°C

**Auto-ignition Temperature (Hydrotreated Light Distillates):** 236°C (456.8°F)

**Lower Explosion Limit:** 0.6%

**Upper Explosion Limit:** 5.5%

**Suitable Extinguishing Media:**

Water fog. Foam. Carbon dioxide (CO2). Alcohol resistant foam. Powder. Dry chemicals.

**Unsuitable Extinguishing Media:**

Water. Do not use water jet as an extinguisher, as this will spread the fire.

**Products of Combustion:**

May produce irritating, corrosive, and or toxic gases.

**Fire Fighting Equipment/Instructions:**

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. Structural firefighters protective clothing will only provide limited protection. In case of fire and/or explosion do not breathe fumes. If tank, rail car or tank truck is involved in a fire, ISOLATE for 800 meters (1/2 mile) in all directions; also consider initial evacuation for 800 meters (1/2 mile) in all directions. ALWAYS stay away from tanks engulfed in flame. Withdraw immediately in case of rising sound from venting safety device or any discoloration of tanks due to fire. Move containers from fire area if you can do so without risk. Cool containers exposed to heat with water spray and remove container, if no risk is involved. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out. In the event of fire and/or explosion do not breathe fumes.

HAZARD	HMIS	NFPA
Toxicity	1	1
Fire	2	2
Reactivity	0	0

**Section 6: ACCIDENTAL RELEASE MEASURES**

**Personal Protection:** Keep unnecessary personnel away. Fully encapsulating, vapor protective clothing should be worn for spills and leaks with no fire. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Keep people away from and upwind of spill/leak. Keep upwind. Keep out of low areas. Ventilate closed spaces before entering them.

**Environmental Precautions:** Prevent further leakage or spillage if safe to do so. Do not contaminate water.

**Method for Containment:** ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area. Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Use water spray to reduce vapors or divert vapor cloud drift. Prevent entry into waterways, sewer, basements or confined areas.

Large Spills: Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Small Spills: Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

**Methods for Clean-up:** Ventilate area of leak or spill. Use spark-proof tools to sweep or scrape up and containerize in approved chemical waste container.

**Section 7: HANDLING AND STORAGE**

**Handling:**

DO NOT handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. Do not smoke. All equipment used when handling the product must be grounded. Do not breathe

dust/fume/gas/mist/vapors/spray. Avoid prolonged or repeated contact with skin. Wear personal protective equipment. Do not use in areas without adequate ventilation. Wash thoroughly after handling. Avoid release to the environment.

**Storage:**

Store locked up. The pressure in sealed containers can increase under the influence of heat. Keep away from heat and sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a well-ventilated place. Keep container tightly closed. Keep out of the reach of children.

## Section 8: EXPOSURE CONTROLS/ PERSONAL PROTECTION

**Engineering Controls:** Ensure adequate ventilation, especially in confined areas.

**Personal Protective Equipment (PPE)**

**Respiratory Protection:** Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

**Eye/Face Protection:** Chemical goggles. Face-shield. Eye wash fountain is recommended.

**Hand Protection:** Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

**Body:** Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

**Other Protective Equipment:**

When using do not smoke. Keep away from food and drink. Handle in accordance with good industrial hygiene and safety practice.

See section 3 for exposure limits.

## Section 9: PHYSICAL AND CHEMICAL PROPERTIES

**Appearance, State:** Product is water-white to pale straw liquid.

**Color:** Colorless to pale straw

**Odor:** Hydrocarbon

**pH:** Not Available

**Vapor Density Hydrotreated Light Distillates (petroleum):** 4.5 [Air=1]

**Boiling Point Hydrotreated Light Distillates (petroleum):** >374°F

**Vapor Pressure Hydrotreated Light Distillates (petroleum):** 0.54 mm of Hg (@room temperature)

**Freezing point Hydrotreated Light Distillates (petroleum):** -58°C (-72.4°F)

**Flash Point** (See Section 5)

**Flammability Properties** (See section 5)

**Solubility** (in water) Negligible

**Specific Gravity Hydrotreated Light Distillates (petroleum):** 0.78

**Evaporation Rate Hydrotreated Light Distillates (petroleum):** 0.03

**Octanol/Water partition coefficient (Kow):** Not Available

**Auto-ignition temperature:** Not Available

**Decomposition temperature:** Not Available

**Viscosity:** Kinematic (40ac (104aF)): 0.0134 cm<sup>2</sup>/s (1.34 cSt)

## Section 10: STABILITY AND REACTIVITY

**Stability:** This material is considered stable at ambient temperatures 70°C (21°C).

**Condition to Avoid:** Heat, flames and sparks. Avoid temperatures exceeding the flash point.

**Incompatible Materials:** Oxidizing materials

**Hazardous Decomposition:** Not Available

**Hazardous Reactions:** This product will not undergo polymerization.

## Section 11: TOXICOLOGICAL INFORMATION

### ACUTE EFFECTS:

#### Component Analysis LD50

Hydrotreated Light Distillates (petroleum) (64742-47-8)

Acute Dermal LD50 Rabbit: > 2000 mg/kg

Acute Oral LD50 Rat: > 5000 mg/kg

### CHRONIC EFFECTS:

#### Component

Hydrotreated Light Distillates (petroleum) (64742-47-8)

**Carcinogenic Effects NTP:** Not a carcinogen by IARC, ACGIH, NTP, or OSHA.

**Mutagenic Effects:** Not Available.

**Teratogenic Effects:** Not Available

**Developmental Toxicity:** Not Available

**Target Organs:** Toxic by inhalation.

**Routes of exposure** Inhalation.

**Eyes** Causes eye irritation. Avoid contact with eyes.

**Skin** Avoid contact with the skin. Causes skin irritation.

**Inhalation** Toxic by inhalation. Can cause central nervous system (CND) depression. Do not breathe dust/fume/gas/mist/vapors/spray.

**Ingestion** Do not ingest. Ingestion can cause gastrointestinal irritation, nausea, vomiting and diarrhea. Aspiration hazard if swallowed. Can cause central nervous system (CND) depression.

## Section 12: ECOLOGICAL INFORMATION

**Ecotoxicity:** Hydrotreated Light Distillates (petroleum) (64742-47-8)

LC50 Rainbow trout, Donaldson trout (*Oncorhynchus mykiss*): 2.9 mg/l 96 hours

## Section 13: DISPOSAL CONSIDERATIONS

Dispose of in accordance with local, state, and federal regulations.

## Section 14: TRANSPORT INFORMATION

**Proper Shipping Name:** Petroleum Distillates, n.o.s.

**Hazard Class:** 3

**Identification No.:** UN1268

**Packing Group:** III

**Label:** Flammable

## Section 15: REGULATORY INFORMATION

**TSCA Inventory** This product and/or its components are listed on the Toxic Substances Control Act (TSCA) inventory.

**SARA 302/304** The Superfund Amendments and Reauthorization Act of 1986 (SARA) Title III requires facilities subject to Subparts 302 and 304 to submit emergency planning and notification information based on Threshold Planning Quantities (TPQs) and Reportable Quantities (RQs) for "Extremely Hazardous Substances" listed in 40 CFR 302.4 and 40 CFR 355. No components were identified.

**SARA 313:** No components were identified.

**CERCLA** The Comprehensive Environmental Response, Compensation, and Liability Act of 1980 (CERCLA) requires notification of the National Response Center concerning release of quantities of "hazardous substances" equal to or greater than the reportable quantities (RQ's) listed in 40 CFR 302.4. As defined by CERCLA, the term "hazardous substance" does not include petroleum, including crude oil or any fraction thereof which is not otherwise specifically designated in 40 CFR 302.4. Chemical substances present in this product or refinery stream that may be subject to this statute are: No components were identified.

**SARA 311/312 Hazard** The Superfund Amendments and Reauthorization Act of 1986 (SARA) Title III requires facilities subject to this subpart to submit aggregate information on chemicals by "Hazard Category" as defined in 40 CFR 370.2. This material would be classified under the following hazard categories: Immediate (Acute) Health Hazard, Chronic Health Hazard, Fire Hazard

**California Prop 65:** No components were identified.

## **Section 16: OTHER SUPPLEMENTAL INFORMATION**

**Prepared by: Multi-Tech Corp. on 6/24/14**

**Disclaimer:**

The information and recommendations contained in the Safety Data Sheet (SDS) are supplied pursuant to 29 CFR 1910.1200 of the Occupational Safety and Health Standards Hazard Communication Rule. The information and recommendations set forth herein are presented in good faith and believed to be correct as of this date hereof.

Multi-Tech, however, makes no representation as to the completeness or accuracy thereof, and information is supplied upon the express condition that the persons receiving the information will be required to make their own determination as to its suitability for their purposes prior to use. In no event will Multi-Tech be responsible for any damages of any nature whatsoever resulting from the use of, reliance upon, or the misuse of this information. User assumes all risk of use, storage and handling of the product in compliance with applicable federal, state and local laws and regulations.

NO REPRESENTATIONS OR WARRANTIES, EITHER EXPRESSED OR IMPLIED, OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR OF ANY OTHER NATURE, ARE MADE BY MULTI-TECH HEREUNDER WITH RESPECT TO INFORMATION OR THE PRODUCT TO WHICH THE INFORMATION REFERS. The information as supplied herein is simply to be informative and intended solely to alert the user of the substance which is the subject matter of this SDS. The ultimate compliance with federal, state or local regulations concerning the use of this compound, or compliance with respect to product liability, rests solely upon the purchaser thereof.

This information relates to the material designated and may not be valid for such material used in combination with any other materials nor in any process.