

MATERIAL SAFETY DATA SHEET

1: CHEMICAL PRODUCT IDENTIFICATION

Product Name: **ID-CITRA-CLEAN Screen Wash**
Manufactured for: Lawson Screen Products, Inc. 5110 Penrose Street, Saint Louis, MO 63115 USA
General Information: 314-644-1300
Emergency Phone: CHEMTREC 1-800-424-9300
MSDS Date: June 1, 2006

2: COMPOSITION, INFORMATION ON INGREDIENTS

Component	CAS REG. NO.	OSHA PEL/TWA	OSHA STEL	ACGIH TLV	ACGIH STEL
Limonene	5989-27-5	100 ppm	NE	100 ppm	NE
Alkylarylethoxylate	68412-54-4	300 ppm	NE	300 ppm	NE

3: HAZARDS IDENTIFICATION

EMERGENCY RESPONSE INFORMATION

Hazards: HMIS/NFPA- Toxicity=1, Fire=2, Reactivity=1

HEALTH EFFECTS FROM OVEREXPOSURE

Primary Routes of Exposure

Eye Contact: Direct contact with material can cause severe irritation, pain and corneal injury.

Skin Contact: May cause irritation with prolonged or repeated contact. Removes natural oils and fats from skin.

Inhalation: Inhalation of mist or spray can cause irritation to nose, throat and lungs, and higher concentrations may cause headaches, nausea, dizziness, drowsiness and other central nervous system effects.

Ingestion: This material is of a low order of toxicity. It may cause headache, dizziness, gastrointestinal distress.

4: FIRST AID MEASURES

Inhalation: Remove subject to fresh air. Keep subject at rest. If not breathing, give artificial respiration. Obtain medical assistance.

Eye Contact: Immediately flush eyes with a large amount of water for at least 15 minutes, forcibly holding eyelids apart to ensure complete irrigation of all eye and lid tissues. Remove contact lenses if worn. Consult a physician.

Skin Contact: Wash affected skin areas thoroughly with soap and water for 15 minutes until no odor remains. If redness or swelling develops, consult a physician. Immediately remove contaminated clothing and wash before reuse.

Ingestion: NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON. Have person drink several glasses of water. Do not induce vomiting. Keep airway clear. Keep subject at rest. Obtain Emergency Medical Attention.

5: FIRE FIGHTING MEASURES

FIRE AND EXPLOSIVE PROPERTIES:

Flash Point: 110°F TCC = 43.3°C

Auto-ignition Temperature: 525°F = 274°C Estimated

Lower Explosion Limit: 0.7 % Volume Estimated

Upper Explosion Limit: 6.1 % Volume Estimated

Unusual Hazards: Combustible liquid; will release invisible vapors that form combustible mixtures that might ignite or explode under some conditions. Vapors can travel considerable distances to an ignition source and flash back. Toxic gasses will form upon combustion. Material will partially disperse and then float on water. Rags, cloth or cardboard which is soaked with product can spontaneously combust. Do not dispose of solvent soaked materials in an open dumpster or trash can; store in an approved covered waste can or soak materials with water. Failure to properly dispose of soaked materials can cause a fire.

Extinguishing Agents: Water spray, regular foam, dry chemical, carbon dioxide are appropriate. Use extinguishing media appropriate for surrounding media. Avoid spraying water directly into storage containers due to danger of boil-over. Use water spray to cool adjacent fire exposed containers to avoid rupture and spattering.

5: FIRE FIGHTING MEASURES (Continued)

Personal Protective Equipment: Keep personnel removed and upwind. As in any fire, wear self-contained breathing apparatus (pressure demand, MSHA/NIOSH approved or equivalent) and full protective gear. Special Procedures: Water may spread the fire.

6: ACCIDENTAL RELEASE MEASURES

Personal Protection: Appropriate protective equipment must be worn when handling a spill of this material. See the PERSONAL PROTECTION MEASURES Section for recommendations. If exposed to material during clean-up operations, see the FIRST AID PROCEDURES Section for appropriate actions.

Procedures: Prevent ignition; stop leak; ventilate area; keep spectators away; contain spill immediately with inert noncombustible materials (e.g. sand, earth, absorbent). Transfer liquids and solid diking material to separate suitable containers for recovery or disposal. CAUTION: Keep spills and cleaning runoff out of municipal sewers, watercourses and open bodies of water. Use water spray to disperse vapors.

7: HANDLING AND STORAGE

Handling: Avoid contact with skin, eyes or clothing. Avoid breathing of mist or vapor.

Storage Conditions: Keep away from heat, sparks and open flame. Protect from storage temperatures above 120°F. Keep in a well ventilated space that is NFPA Class 1C. Consult NFPA and OSHA codes. Transfer operations must be electrically grounded. Keep Out of Reach of Children. Store upright in original closed container.

"Empty" containers retain product residue (liquid and/or vapor) that can be dangerous. Empty drums should be completely drained and properly bunged and promptly returned to a reconditioner or other proper disposal.

8: EXPOSURE CONTROLS, PERSONAL PROTECTION

Respiratory Protection: A respiratory program meeting OSHA 1910.134 and ANSI Z88.2 requirements must be followed whenever workplace conditions warrant a respirator's use. Use of this product does not require respiratory protection under normal operating conditions but use of local exhaust ventilation is recommended, especially for confined spaces. Where vapors or mists may occur, wear a MSHA / NIOSH approved (or equivalent) half-mask air purifying respirator. Air purifying respirators should be equipped with organic vapor cartridges and dust and mist filters.

Eye Protection: Wear chemical splash goggles (ANSI Z87.1 or approved equivalent), or full-face shield.

Hand Protection: Wear gloves resistant to solvent permeation: neoprene, nitrile, polyvinyl alcohol, viton.

Other Protection: None required.

FACILITY CONTROL MEASURES:

Ventilation: Use with adequate ventilation. Local exhaust ventilation is recommended and explosion equipment is required.

Other Protective Equipment: facilities storing or utilizing this material should be equipped with eyewash and safety shower facilities.

9: PHYSICAL AND CHEMICAL PROPERTIES - TYPICAL

State	Liquid	Vapor Density (Air = 1)	< 1
Chemical Formula	Mixture	Vapor Pressure	< 1 mm Hg @ 20°C
Appearance	Clear	Freezing Point	< -73°F = -100°F
Color	Colorless to pale amber	Boiling Point	160°C = 320°F initial
Odor	Characteristic citrus	Solubility in Water	emulsifiable
Viscosity	Thin < 5 cSt @ 25°C	Percent Volatility	90%
pH as is	Slightly acidic in water	VOC %	90% = 6.48 Lbs/Gal
Specific Gravity @ 60°F	0.865	Kauri-Butanol Value	> 70
Density @ 60°F	7.2 Lbs/Gal	Refractive Index @ 20°C	1.4735 typical

10: STABILITY AND REACTIVITY

Instability: This material is considered stable.

Hazardous Decomposition Products: There are no known hazardous decomposition products for this material except for Carbon Dioxide, Carbon Monoxide if burned.

Hazardous Polymerization: This product will not undergo polymerization. Incompatibility: This product is not compatible with strong acids and strong oxidizing agents.

11: TOXICOLOGICAL INFORMATION

Inhalation of large quantities of vapor for extended periods is presumed to be harmful: Overexposure to high concentrations can cause eye, nose, throat, lung irritation; dizziness, difficulty in breathing, unconsciousness. Information available on the chronic health effects from long term exposure is limited. Skin contact can incur absorption. Repeated or prolonged contact is irritating.

Eye contact is irritating. Oral consumption is harmful if swallowed. Pulmonary aspiration can enter lungs and cause damage.

12: ECOLOGICAL INFORMATION

Toxic to fish and food organisms.

13: DISPOSAL CONSIDERATIONS

Procedure: Incinerate liquid and contaminated solids in accordance with local, state and federal regulations.

14: TRANSPORTATION INFORMATION

Proper Shipping Name: Combustible Liquid, n.o.s. (Contains Limonene), NA1993, PG III

Emergency Response Guide No.: 27/128

Per 49 CFR 173.150 (f) the hazardous material requirements for non-bulk packaging such as drums and pails and cases need not apply except for aircraft transportation.

15: REGULATORY INFORMATION

WORKPLACE CLASSIFICATIONS

This product is considered to be hazardous under the OSHA Hazard Communication Standard (29 CFR 1910.1200). This product is a 'controlled' product under the Canadian Workplace Hazardous Materials Information System (WHMIS).

Class B - Division 3; Combustible Liquid

Class D - Division 2B

EMERGENCY PLANNING AND COMMUNITY RIGHT - TO KNOW (SARA TITLE III)

Section 311/312 Categorizations (40 CFR 370): This product is a hazardous material under 29 CFR 1910.1200, and therefore is covered by Title III of SARA and is classified into the following hazard categories: Fire

15: REGULATORY INFORMATION (Continued)

Section 313 Information (40 CFR 372): This product is not a chemical which is listed in Section 313 at or above the de minimis concentrations. CERCLA INFORMATION (40 CFR 302.4): Releases of this material to air, land or water are not reportable to the National Response Center under the Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA) or to the state and local emergency planning committees under the Superfund Amendments and Reauthorization Act (SARA) Title III Section 304.

RCRA INFORMATION: When a decision is made to discard this material as supplied, it does meet RCRA's characteristic definition of ignitability.

CHEMICAL CONTROL LAW STATUS: All components of this product are listed or are excluded from listing on the U.S. Toxic Substances Control Act (TSCA) Chemical Substance Inventory. This Mixture is not considered to be a carcinogen by IARC or NTP. This Mixture is a by product of base materials that are entirely of natural vegetable origin. Solvent does NOT contain and is NOT manufactured with any of the Class I or Class II ozone depleting substances listed under the US Clean Air Act of 1990.

16: OTHER SUPPLEMENTAL INFORMATION

ABBREVIATIONS

ACGIH	American Conference of Governmental Industrial Hygienists
OSHA	Occupational Safety and Health Administration
TLV	Threshold Limit Value
PEL	Permissible Exposure Limit
TWA	Time Weighted Average
STEL	Short Term Exposure Limit
BAC	Butyl acetate
NE	Not Established
ND	Not Determined
NA	Not Applicable

The information contained herein pertains only to the specific material identified. Lawson Screen Products, Inc. believes that such information and recommendations set forth herein are accurate and reliable as of the date of this material safety data sheet, but Lawson Screen Products Inc. makes no representation as to the completeness or accuracy thereof and supplies the information upon the condition that the persons receiving same will make their own determination as to its suitability for their purpose prior to use. In no event will Lawson Screen Products, Inc. be responsible for any damage of any nature whatsoever resulting from the use of or reliance upon this information. No representation, guarantee or warranty, either express or implied, is made hereunder as to the accuracy, reliability, completeness of the information, of merchantability, of fitness for a particular purpose or of any other nature, with respect to information or the product to which it refers.